

The Bush-Whacker 6010 & 7210

5 and 6 Foot Rotary Cutters

Bush-Whacker mowers from Hall Manufacturing have been popular for decades for highway right-of-way use. Lately, they have been increasingly in demand for agricultural, commercial and other applications where a heavy-duty, rugged mower is needed. The Bush-Whacker is available in a range of sizes to fit your needs — from the five-foot model all the way to the big 20-footer.

Hall Manufacturing has been in business for more than 75 years. During this time they've sold more than 10,000 units and are used in 27 states in the U.S.



- **3 point hitch or pull type**
- **3/16" Deck**
- **Structural frame of mower is 2" by 3" tubing with 1/4" wall thickness**
- **1/4" I-Beam sides instead of 1/4" flat steel**
- **Gearbox is mounted to a 1/2" plate that is welded to the 3/16" deck**
- **6 bolt mounting on gearbox — heads are tack-welded to bottom of deck so one man can tighten the nuts or change the gearbox**



Hall Manufacturing

3706 East Washington • P.O. Box 5652 • North Little Rock, AR 72119

PH: 501-945-7550

• www.bush-whacker.com



Model 6010 — 5 Foot Rotary Cutter

Model 7210 — 6 Foot Rotary Cutter

SPECIFICATIONS*

Gearbox — 150 HP, 540 or 1,000 RPM, Base Mounted, 1:1.47 Ratio

Malleable housing; forged alloy steel; carburized and hardened gears and shafts; 20 splined 1 3/4" input shaft, 2 1/8" output shaft; tapered bearings; lifetime lubricated.

Slip Clutch

Heavy duty spring-type adjustment with four friction discs.

Shielded PTO — Category 4

Made from finest quality propeller shaft materials and needle bearing universal joints.

Blades

1/2" material, alloy spring steel, airlift design, free swinging for long life and clean cutting. Swings back when encountering obstructions, mounted on shoulder bolts.

Tail Wheel —

For 3-point hitch: Extra heavy duty, tapered bearings, 4" by 8" laminated puncture-proof tire.

For pull type: Extra heavy duty, tapered bearings, two 6" by 9" laminated puncture-proof tire.

Cutting Height — 2" to 13"

Turner Special Deck — 3/16" Material

Heavy duty, one-piece electric welded frame, rolled I-Beam sides, mechanical tubing structurals.

Rolled I-Beam Sides — 1/4" Material

Shaped to form sides of cutter

Chain Guards Front and Rear

Heavy Duty Category One or Two Hitch

Weight:

Model 7210 — 1130 lb.

Model 6010 — 860 lb.

*These specifications are standard; however, any State Department of Transportation Specifications that may differ from standard Bush-Whacker Specifications will take precedence and be implemented into production.

WARRANTY: Guaranteed for 12 months against defective materials and workmanship. Defective parts must be returned prepaid to the factory. Guarantee is void if failure is due to operators negligence, abuse or using other than genuine Bush-Whacker parts.

