

MANITOU

K-D Hawk



- Lift Capacity: 6,000 lb.
- Lift Heights to 12 ft. 4 in.
- Two Cab Heights
- Special Poultry Features



 **MANITOU**

K-D HAWK



Lift Capacity

Maximum (24 in. load center) 6,000 lb.
 Maximum (48 in. load center) 3,600 lb.



Lift Height:

Max. lift height 148 in.



Tires:

Standard Drive (Front) 81"/100" . . . 17.5L24 x 12
 Standard Drive (Front) 77"15 x 19.5
 Standard Steer (Rear)12 x 16.5



Forks:

Length84 in.
 Width5 in.
 Thickness 1.75 in.



Brakes:

Service . . . Fully enclosed, oil-immersed disc type
 Parking brake Mechanical



Engine Options:

Model Caterpillar or Perkins
 Type Diesel
 Displacement 4 cyl. - 236 cu. in.
 Power 80 HP
 Rated Speed 2200 RPM



Transmission Options:

Type Hydrostatic or Torque Convertor
 Max. travel speed 16 mph



Hydraulics:

Pump Gear type
 Flow 25 gpm



Capacities:

Cooling system 5 gal.
 Engine oil 2.75 gal.
 Fuel tank 26 gal.
 Hydraulic fluid 26 gal.



Specifications:

Weight 14,500 lb.
 Turning radius (center of wheels) 117 in.
 Overall length (without forks) 149 in.

Mast Selections & Capacities

(Based on 48 in. Load Center)

MFH	CAPACITY	
	148"	3,600 lb.
	135"	3,600 lb.
OHL	77"	81"
MFH	135"	148"
FFH	16"	16"

3-Stage Low-Profile "Total Visibility" Roller Mast with Optional Rotator Carriage

DIMENSIONS:...

100"81" ...77"
 A.....8484.....84
 B.....8585.....85
 C3737.....37
 D150150.....150
 E.....234234.....234
 F...70.570.5...66.5
 F₁...71.571.5...68.5
 G1313.....12
 G₂...9.59.5.....9.5
 I.....2828.....28
 U10081.....77
 W...87.587.5.....82
 Y10°10°10°
 Z45°45°45°
 (with rotator attachment)

STANDARD EQUIPMENT:

- 80 H.P. Four Cylinder Diesel Engine
- 2 Wheel Drive
- Heavy Duty Steer Axle
- Side Shift Mast
- Hydraulic Load Accumulator
- 4 Spool Hydraulic Valve Assembly
- Rubber Mounted Tilting Operator's Compartment
- Gauge Package
- Poultry Light Package
- Backup Alarm
- Tow Pin

OPTIONAL EQUIPMENT:

- Semi-Enclosed Cab
- Rotator Carriage
- 4 Wheel Drive

