



Trenchers are one of the most common attachments for a skid steer loader. Various chain types are available to suit the soil type and size of the project. Trenchers have a double-flighted spoil auger and excellent wear resistance on the drive sprocket. Increase the productivity of your skid-steer loader with a trencher attachment!

Use a single standard chain in loose, damp conditions. Double standard, ABF (anti-back flex) chains are recommended for harder, drier conditions. Rock and frost chains are used for harder soil and mixed rocky conditions. In many configurations, these trenchers are available in widths up to 12" and depths up to 60". Contact CEAttachments for availability of configurations not shown.



Various Widths



Rock and Frost Chain

- ◎ **VARIOUS CHAIN STYLES AND WIDTHS AVAILABLE**
- ◎ **TAPERED ROLLER NOSE BEARINGS FOR MINIMUM MAINTENANCE**
- ◎ **OPTIONAL HYDRAULIC SIDE-SHIFT**

SPECIFICATIONS

| Model | Hyd. Req. (gpm/lpm) | Depths Available (in/mm) | Working Width (in/mm) | Productivity (ft/m per minute) |
|-------|------------------------|--------------------------|-----------------------|-----------------------------------|
| XR14 | 10-20/38-75 | 24-48/609-1215 | 6-12/152-305 | 326/99 |
| XR21 | 13-25/49-94 | 24-60/609-1524 | | 278/85 |
| XR25 | 16-25/61-96 | | | 263/80 |
| XR35 | 20-40/76-151 | | | 333/101 |