

The Bush-Whacker ST-120 2010

10-Foot Smooth Deck Flex-Wing Rotary Cutter

Bush-Whacker mowers from Hall Manufacturing are increasing in demand for agricultural, commercial and other applications where a heavy-duty, rugged mower is needed. The Bush-Whacker is available in a range of sizes to fit your needs - from the five foot model all the way to the big 20-footer.



Hall Manufacturing has been in business for more than 75 years. During this time they've sold more than 10,000 units across the U.S.

- **Structural frame of mower is 3" channel, 1/4" thick**
- **8-bolt mounting on gearboxes - heads are tack-welded to bottom of deck so one person can tighten the nuts or change the gearbox.**
- **Blades are 1/2" by 4" instead of traditional 1/2" by 3 1/2"**
- **Hinges -- 3" by 4" tubing with grease fittings**



Bush-Whacker® Hall Manufacturing
KICKS GRASS!
3706 East Washington • PH: 501-945-7550

• P.O. Box 5652 • North Little Rock, AR 72119
• www.bush-whacker.com



Bush-Whacker®

Model ST-120 Elite - 10-Foot Smooth Deck Flex-Wing Rotary Cutter

Specifications*

Gearboxes — 540 RPM or 1,000 RPM Two spindle gearboxes, 250 HP, base mounted, 1:1.6 ratio. One dividerbox, 275 HP, base mounted. All gearboxes have malleable housings, forged alloy steel, carburized and hardened gears and shafts, tapered and ball bearings. 20 splined 1 3/4" input shaft, 2 3/8" output shaft on spindle boxes.

Drive Shafts Shielded PTOs made from finest quality propeller shaft materials and needle bearing universal joints. Category 5 80-degree constant velocity main drive shaft, Category 4 intermediate and wing drive shafts.

Slip Clutch Two heavy-duty clutches with spring type adjustment and four friction discs.

Blades 1/2" by 4" material, alloy spring steel, airlift design. Free swinging when encountering obstructions. 8" overlap for better cutting. Blade tip speed: 16,768 FPM.

Wheels Five solid rubber tires standard. Independent shock absorbing system for all wheel axles. Cutting height adjustable from 2" to 17". Optional: aircraft tires or implement tires.

Bush-Whacker Special Deck Bush-Whacker Special Deck includes a primary (bottom) deck of 3/16" steel that is welded to heavy duty heavy channel structures. The smooth, easy-to-clean top deck is made of 12 gauge steel and protects the inner support frame. Combined deck thickness: .2921".

Hydraulic Adjustments Hydraulic lift cylinders control raising and lowering of flexible wing (winch assembly for manual wing lift is optional). Wing may be raised to 88 degrees above horizontal and lowered to 22 degrees below horizontal cutting plane. Optional: rephasing level lift systems.

Chain Guards Front and Rear

Dimensions Cutting width: 10'. Cutting height: adjustable from 2" to 15". Overall width: 140". Overall length: 167". Transportation width: 80". Cutting height for aircraft and implement tires: 2" to 17".

Weight Without chains and tires: 4,260 lb.
Total weight: 4,980 lb.

Other Standard Features Include: Replaceable center and full length wing skid shoes, transport locking bars for each wing, heavy-duty tongue assembly with dual leveling rods, hydraulic hose holder, jack for easy hookup and unhooking from tractor.

**These specifications are standard; however, any State Department of Transportation Specifications that may differ from standard Bush-Whacker Specifications will take precedence and be implemented into productions*

WARRANTY: Guaranteed for 12 months against defective materials and workmanship. Defective parts must be returned prepaid to the factory. Guarantee is void if failure is due to operators negligence, abuse or using other than genuine Bush-Whacker parts.

